

If actual load on tyre or axle, and maximum load of tyre, is given exact the pressure advice is save.

The maximum load given by the tyre-maker is their responsibility, and for some times this is to high given (low aspect ratio and off-road tyres).

Determining the right actual load is your responsibility, and this is often judged to low. Also misreadings (use a light).

If in red, the pressure is higher then the reference-pressure (maxloadpressure further Pr) wich is not the maximum pressure, written on sidewall (44 to 51 psi)

Difference between Pr and maximum pressure is used for higher speed and camber-angle so tire-maker does not support this higher load (only for low speed).

for all American tires of this kind

		35 PSI		2.4 bar		Standard load/SL/P-tire										given per tire		For Single-Load			
ML=maximum load,LI=Loadindex						Up to maximum speed of tire, or if lower 160km/99m/h, and camber angle below 2 degr.															
LI	66	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	661	<LBS>	280	315	350	385	420	455	490	525	555	590	625	661	710	760	810	860			
LI	67	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	677	<LBS>	285	325	360	395	430	465	500	535	570	605	640	677	725	780	830	880			
LI	68	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	694	<LBS>	295	330	370	405	440	475	515	550	585	620	655	694	745	795	850	900			
LI	69	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	717	<LBS>	300	340	380	420	455	495	530	565	605	640	680	717	770	825	880	930			
LI	70	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	739	<LBS>	315	350	390	430	470	510	545	585	625	660	700	739	795	850	905	960			
LI	71	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	761	<LBS>	320	365	405	445	485	525	565	600	640	680	720	761	815	875	930	990			
LI	72	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	783	<LBS>	330	375	415	455	500	540	580	620	660	700	740	783	840	900	960	1020			
LI	73	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	805	<LBS>	340	385	425	470	510	555	595	635	680	720	760	805	865	925	985	1045			
LI	74	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	827	<LBS>	350	395	440	480	525	570	610	655	695	740	780	827	890	950	1015	1075			
LI	75	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	853	<LBS>	360	405	450	495	540	585	630	675	720	765	805	853	915	980	1045	1110			
LI	76	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	882	<LBS>	375	420	470	515	560	605	655	700	745	790	835	882	945	1015	1080	1145			
LI	77	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	908	<LBS>	385	435	480	530	575	625	670	720	765	815	860	908	975	1045	1115	1180			
LI	78	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	937	<LBS>	395	450	495	545	595	645	695	740	790	840	885	937	1005	1075	1150	1220			
LI	79	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	963	<LBS>	405	460	510	560	610	665	715	765	810	860	910	963	1035	1105	1180	1255			
LI	80	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	992	<LBS>	420	475	525	580	630	685	735	785	835	890	940	992	1065	1140	1215	1290			
LI	81	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1019	<LBS>	430	485	540	595	650	700	755	805	860	910	965	1019	1095	1170	1250	1325			
LI	82	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1047	<LBS>	445	500	555	610	665	720	775	830	885	935	990	1047	1125	1205	1285	1365			
LI	83	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1074	<LBS>	455	515	570	625	685	740	795	850	905	960	1015	1074	1155	1235	1315	1400			
LI	84	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1102	<LBS>	470	525	585	645	700	760	815	875	930	985	1045	1102	1185	1270	1350	1435			
LI	85	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1135	<LBS>	480	545	605	665	720	780	840	900	960	1015	1075	1135	1220	1305	1390	1475			
LI	86	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1168	<LBS>	495	560	620	680	745	805	865	925	985	1045	1105	1168	1255	1345	1430	1520			
LI	87	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1202	<LBS>	510	575	640	700	765	830	890	955	1015	1075	1140	1202	1290	1385	1475	1565			
LI	88	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1235	<LBS>	525	590	655	720	785	850	915	980	1045	1105	1170	1235	1325	1420	1515	1610			
LI	89	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1279	<LBS>	540	610	680	745	815	880	950	1015	1080	1145	1210	1279	1375	1470	1570	1665			
LI	90	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1323	<LBS>	560	635	705	775	840	910	980	1050	1115	1185	1255	1323	1420	1520	1625	1720			
LI	91	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1356	<LBS>	575	650	720	790	865	935	1005	1075	1145	1215	1285	1356	1455	1560	1665	1765			
LI	92	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1389	<LBS>	590	665	740	810	885	955	1030	1100	1175	1245	1315	1389	1495	1600	1705	1810			
LI	93	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1433	<LBS>	605	685	760	835	915	985	1060	1135	1210	1285	1355	1433	1540	1650	1760	1865			
LI	94	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1477	<LBS>	630	705	785	865	940	1020	1095	1170	1245	1325	1400	1477	1585	1700	1810	1925			
LI	95	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1521	<LBS>	645	730	810	890	970	1050	1125	1205	1285	1365	1440	1521	1635	1750	1865	1980			
LI	96	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1565	<LBS>	665	750	830	915	995	1080	1160	1240	1320	1400	1485	1565	1680	1800	1920	2040			
LI	97	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1609	<LBS>	680	770	855	940	1025	1110	1195	1275	1360	1440	1525	1609	1730	1850	1975	2095			
LI	98	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1653	<LBS>	705	790	880	965	1055	1140	1225	1310	1395	1480	1565	1653	1775	1905	2030	2155			
LI	99	PSI>	13	15	17	19	21	23	25	27	29	31	33	35	38	41	44	47			
ML	1709	<LBS>	725	820	910	1000	1090	1180	1265	1355	1445	1530	1620	1709	1835	1965	2095	2225			
LI	100	PSI>	13	15	17	19	21	23	25	27											

If actual load on tyre or axle, and maximum load of tyre, is given exact the pressure advice is save.

The maximum load given by the tyre-maker is their responsibility, and for some times this is to high given (low aspect ratio and off-road tyres).

Determining the right actual load is your responsibility, and this is often judged to low. Also misreadings (use a light).

If in red, the pressure is higher then the reference-pressure (maxloadpressure further Pr) wich is not the maximum pressure, written on sidewall (44 to 55 psi)

Difference between Pr and maximum pressure is used for higher speed and camber-angle so tire-maker does not support this higher load (only for low speed).

for all American tires of this kind

			41 PSI 2.8 bar		Extraload/reinforced/XL given per tire														For Single-Load			
ML=maximum load, LI=Loadindex			Up to maximum speed of tire, or if lower 160km/99m/h, and camber angle below 2 degr.																			
LI	66	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	661	<LBS>	335	365	395	425	455	485	510	540	570	600	630	661	690	715	745	775				
LI	67	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	677	<LBS>	340	370	405	435	465	495	525	555	585	615	645	677	705	735	765	795				
LI	68	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	694	<LBS>	350	380	415	445	475	505	540	570	600	630	660	694	720	750	785	815				
LI	69	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	717	<LBS>	360	395	425	460	490	525	555	590	620	650	685	717	745	775	810	840				
LI	70	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	739	<LBS>	375	405	440	475	505	540	575	605	640	670	705	739	770	800	835	865				
LI	71	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	761	<LBS>	385	420	455	490	520	555	590	625	660	690	725	761	790	825	860	890				
LI	72	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	783	<LBS>	395	430	465	500	535	570	605	640	675	710	745	783	815	850	885	920				
LI	73	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	805	<LBS>	405	445	480	515	550	590	625	660	695	730	765	805	840	875	910	945				
LI	74	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	827	<LBS>	420	455	495	530	565	605	640	680	715	750	790	827	860	895	935	970				
LI	75	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	853	<LBS>	430	470	510	545	585	625	660	700	740	775	815	853	890	925	965	1000				
LI	76	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	882	<LBS>	445	485	525	565	605	645	685	725	765	800	840	882	920	955	995	1035				
LI	77	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	908	<LBS>	460	500	540	580	625	665	705	745	785	825	865	908	945	985	1025	1065				
LI	78	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	937	<LBS>	475	515	560	600	645	685	725	770	810	850	895	937	975	1015	1060	1100				
LI	79	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	963	<LBS>	485	530	575	620	660	705	745	790	835	875	920	963	1005	1045	1085	1130				
LI	80	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	992	<LBS>	500	545	590	635	680	725	770	815	860	900	945	992	1035	1075	1120	1165				
LI	81	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1019	<LBS>	515	560	610	655	700	745	790	835	880	925	970	1019	1060	1105	1150	1195				
LI	82	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1047	<LBS>	530	575	625	670	720	765	815	860	905	950	1000	1047	1090	1135	1180	1230				
LI	83	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1074	<LBS>	540	590	640	690	740	785	835	880	930	975	1025	1074	1120	1165	1215	1260				
LI	84	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1102	<LBS>	555	610	660	705	755	805	855	905	955	1000	1050	1102	1150	1195	1245	1290				
LI	85	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1135	<LBS>	575	625	675	730	780	830	880	930	980	1030	1085	1135	1180	1230	1280	1330				
LI	86	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1168	<LBS>	590	645	695	750	805	855	905	960	1010	1065	1115	1168	1215	1270	1320	1370				
LI	87	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1202	<LBS>	605	665	720	770	825	880	935	985	1040	1095	1145	1202	1250	1305	1355	1410				
LI	88	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1235	<LBS>	625	680	735	795	850	905	960	1015	1070	1125	1180	1235	1285	1340	1395	1450				
LI	89	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1279	<LBS>	645	705	765	820	880	935	995	1050	1105	1165	1220	1279	1335	1390	1445	1500				
LI	90	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1323	<LBS>	670	730	790	850	910	970	1030	1085	1145	1205	1260	1323	1380	1435	1495	1550				
LI	91	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1356	<LBS>	685	750	810	870	930	995	1055	1115	1175	1235	1295	1356	1415	1470	1530	1590				
LI	92	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1389	<LBS>	705	765	830	890	955	1015	1080	1140	1205	1265	1325	1389	1445	1510	1570	1630				
LI	93	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1433	<LBS>	725	790	855	920	985	1050	1115	1175	1240	1305	1365	1433	1495	1555	1620	1680				
LI	94	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1477	<LBS>	750	815	880	950	1015	1080	1150	1215	1280	1345	1410	1477	1540	1605	1670	1735				
LI	95	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1521	<LBS>	770	840	910	975	1045	1115	1180	1250	1315	1385	1450	1521	1585	1650	1720	1785				
LI	96	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1565	<LBS>	795	865	935	1005	1075	1145	1215	1285	1355	1425	1495	1565	1630	1700	1770	1835				
LI	97	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1609	<LBS>	815	890	960	1035	1105	1180	1250	1320	1395	1465	1535	1609	1675	1750	1820	1890				
LI	98	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1653	<LBS>	835	915	990	1060	1135	1210	1285	1360	1430	1505	1580	1653	1725	1795	1870	1940				
LI	99	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47	49				
ML	1709	<LBS>	865	945	1020	1100	1175	1250	1330	1405	1480	1555	1630	1709	1780	1855	1930	2005				
LI	100	PSI>	19	21	23	25	27	29	31	33	35	37	39	41	43	45	47					

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low.

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

5 PSI					C-load/6 ply		D/8 for larger tires		given per tire					For Single-Load				
ML=maximum load, LI=Loadindex																		
LI	95	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1521	<LBS >	745	815	885	960	1030	1100	1170	1240	1310	1380	1450	1521	1655	1795	1930	2065
LI	96	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1565	<LBS >	765	840	915	985	1060	1130	1205	1275	1350	1420	1490	1565	1705	1845	1985	2125
LI	97	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1609	<LBS >	785	865	940	1015	1090	1165	1240	1310	1385	1460	1535	1609	1755	1900	2045	2185
LI	98	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1653	<LBS >	810	885	965	1040	1120	1195	1270	1350	1425	1500	1575	1653	1800	1950	2100	2245
LI	99	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1709	<LBS >	835	915	995	1075	1155	1235	1315	1395	1470	1550	1630	1709	1860	2015	2170	2325
LI	100	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1764	<LBS >	865	945	1030	1110	1195	1275	1355	1440	1520	1600	1680	1764	1920	2080	2240	2400
LI	101	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1819	<LBS >	890	975	1060	1145	1230	1315	1400	1485	1565	1650	1735	1819	1980	2145	2310	2475
LI	102	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1874	<LBS >	915	1005	1095	1180	1270	1355	1440	1530	1615	1700	1785	1874	2040	2210	2380	2550
LI	103	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1929	<LBS >	945	1035	1125	1215	1305	1395	1485	1575	1660	1750	1840	1929	2100	2275	2450	2625
LI	104	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	1984	<LBS >	970	1065	1160	1250	1345	1435	1525	1620	1710	1800	1890	1984	2160	2340	2520	2695
LI	105	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2039	<LBS >	1000	1095	1190	1285	1380	1475	1570	1665	1755	1850	1945	2039	2220	2405	2590	2770
LI	106	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2094	<LBS >	1025	1125	1220	1320	1420	1515	1610	1710	1805	1900	1995	2094	2280	2470	2660	2845
LI	107	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2150	<LBS >	1050	1155	1255	1355	1455	1555	1655	1755	1855	1950	2050	2150	2345	2535	2730	2925
LI	108	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2205	<LBS >	1080	1185	1285	1390	1495	1595	1695	1800	1900	2000	2100	2205	2405	2600	2800	3000
LI	109	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2271	<LBS >	1110	1220	1325	1430	1540	1645	1750	1855	1955	2060	2165	2271	2475	2680	2885	3090
LI	110	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2337	<LBS >	1145	1255	1365	1475	1585	1690	1800	1905	2015	2120	2230	2337	2545	2760	2970	3180
LI	111	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2403	<LBS >	1175	1290	1405	1515	1625	1740	1850	1960	2070	2180	2290	2403	2620	2835	3050	3270
LI	112	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2469	<LBS >	1210	1325	1440	1555	1670	1785	1900	2015	2130	2240	2355	2469	2690	2915	3135	3355
LI	113	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2535	<LBS >	1240	1360	1480	1600	1715	1835	1950	2070	2185	2300	2415	2535	2765	2990	3220	3445
LI	114	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2601	<LBS >	1275	1395	1520	1640	1760	1880	2005	2125	2240	2360	2480	2601	2835	3070	3305	3535
LI	115	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2679	<LBS >	1310	1440	1565	1690	1815	1940	2065	2185	2310	2430	2555	2679	2920	3160	3405	3645
LI	116	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2756	<LBS >	1350	1480	1610	1740	1865	1995	2120	2250	2375	2500	2630	2756	3005	3255	3500	3750
LI	117	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2833	<LBS >	1390	1520	1655	1785	1920	2050	2180	2310	2440	2570	2700	2833	3090	3345	3600	3855
LI	118	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2910	<LBS >	1425	1565	1700	1835	1970	2105	2240	2375	2510	2640	2775	2910	3170	3435	3695	3960
LI	119	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	2998	<LBS >	1470	1610	1750	1890	2030	2170	2310	2445	2585	2720	2860	2998	3270	3540	3810	4075
LI	120	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3086	<LBS >	1510	1655	1800	1945	2090	2235	2375	2520	2660	2800	2945	3086	3365	3645	3920	4195
LI	121	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3197	<LBS >	1565	1715	1865	2015	2165	2315	2460	2610	2755	2905	3050	3197	3485	3775	4060	4350
LI	122	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3307	<LBS >	1620	1775	1930	2085	2240	2395	2545	2700	2850	3005	3155	3307	3605	3905	4200	4500
LI	123	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3417	<LBS >	1675	1835	1995	2155	2315	2475	2630	2790	2945	3105	3260	3417	3725	4035	4340	4645
LI	124	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3527	<LBS >	1730	1895	2060	2225	2390	2555	2715	2880	3040	3205	3365	3527	3845	4165	4480	4795
LI	125	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3638	<LBS >	1785	1955	2125	2295	2465	2635	2800	2970	3135	3305	3470	3638	3965	4295	4620	4950
LI	126	PSI >	22,5	25	27,5	30	32,5	35	37,5	40	42,5	45	47,5	50	55	60	65	70
ML	3748	<LBS >	1835	2015	2190	2365	2540	2715	2885	3060	3230	3405						

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low.

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

		65 PSI				D-load/ 8 ply				E/10 for larger tires				given per tire				For Single-Load			
		Max load																			
LI	95	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1521	<LBS >	795	865	930	995	1065	1130	1195	1260	1325	1390	1455	1521	1625	1735	1840	1945			
LI	96	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1565	<LBS >	820	890	960	1025	1095	1160	1230	1295	1365	1430	1495	1565	1675	1785	1895	2000			
LI	97	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1609	<LBS >	845	915	985	1055	1125	1195	1265	1330	1400	1470	1540	1609	1720	1835	1945	2060			
LI	98	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1653	<LBS >	865	940	1010	1085	1155	1225	1300	1370	1440	1510	1580	1653	1765	1885	2000	2115			
LI	99	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1709	<LBS >	895	970	1045	1120	1195	1270	1340	1415	1490	1560	1635	1709	1825	1945	2065	2185			
LI	100	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1764	<LBS >	925	1005	1080	1155	1235	1310	1385	1460	1535	1610	1685	1764	1885	2010	2135	2255			
LI	101	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1819	<LBS >	955	1035	1115	1190	1270	1350	1430	1505	1585	1660	1740	1819	1945	2075	2200	2325			
LI	102	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1874	<LBS >	985	1065	1145	1230	1310	1390	1470	1550	1630	1710	1790	1874	2005	2135	2265	2400			
LI	103	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1929	<LBS >	1010	1095	1180	1265	1350	1430	1515	1595	1680	1760	1845	1929	2065	2200	2335	2470			
LI	104	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	1984	<LBS >	1040	1130	1215	1300	1385	1475	1560	1645	1730	1815	1895	1984	2120	2260	2400	2540			
LI	105	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2039	<LBS >	1070	1160	1250	1335	1425	1515	1600	1690	1775	1865	1950	2039	2180	2325	2465	2610			
LI	106	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2094	<LBS >	1100	1190	1280	1375	1465	1555	1645	1735	1825	1915	2005	2094	2240	2385	2535	2680			
LI	107	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2150	<LBS >	1130	1220	1315	1410	1505	1595	1690	1780	1875	1965	2055	2150	2300	2450	2600	2750			
LI	108	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2205	<LBS >	1155	1255	1350	1445	1540	1635	1730	1825	1920	2015	2110	2205	2360	2515	2670	2820			
LI	109	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2271	<LBS >	1190	1290	1390	1490	1590	1685	1785	1880	1980	2075	2170	2271	2430	2590	2750	2905			
LI	110	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2337	<LBS >	1225	1330	1430	1535	1635	1735	1835	1935	2035	2135	2235	2337	2500	2665	2830	2990			
LI	111	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2403	<LBS >	1260	1365	1470	1575	1680	1785	1885	1990	2095	2195	2300	2403	2570	2740	2910	3075			
LI	112	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2469	<LBS >	1295	1405	1510	1620	1725	1835	1940	2045	2150	2255	2360	2469	2640	2815	2985	3160			
LI	113	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2535	<LBS >	1330	1440	1555	1665	1775	1880	1990	2100	2210	2315	2425	2535	2710	2890	3065	3245			
LI	114	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2601	<LBS >	1365	1480	1595	1705	1820	1930	2045	2155	2265	2375	2490	2601	2780	2965	3145	3330			
LI	115	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2679	<LBS >	1405	1525	1640	1755	1875	1990	2105	2220	2335	2450	2565	2679	2865	3055	3240	3430			
LI	116	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2756	<LBS >	1445	1570	1690	1810	1925	2045	2165	2285	2400	2520	2635	2756	2950	3140	3335	3530			
LI	117	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2833	<LBS >	1485	1610	1735	1860	1980	2105	2225	2345	2470	2590	2710	2833	3030	3230	3430	3625			
LI	118	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2910	<LBS >	1530	1655	1785	1910	2035	2160	2285	2410	2535	2660	2785	2910	3115	3320	3520	3725			
LI	119	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	2998	<LBS >	1575	1705	1835	1965	2095	2225	2355	2485	2610	2740	2870	2998	3205	3420	3630	3840			
LI	120	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3086	<LBS >	1620	1755	1890	2025	2160	2290	2425	2555	2690	2820	2950	3086	3300	3520	3735	3950			
LI	121	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3197	<LBS >	1680	1820	1960	2100	2235	2375	2510	2650	2785	2925	3060	3197	3420	3645	3870	4095			
LI	122	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3307	<LBS >	1735	1880	2025	2170	2315	2455	2600	2740	2880	3025	3165	3307	3540	3770	4000	4235			
LI	123	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3417	<LBS >	1795	1945	2095	2240	2390	2540	2685	2830	2980	3125	3270	3417	3655	3895	4135	4375			
LI	124	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3527	<LBS >	1850	2005	2160	2315	2465	2620	2770	2925	3075	3225	3375	3527	3775	4020	4270	4515			
LI	125	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3638	<LBS >	1910	2070	2230	2385	2545	2700	2860	3015	3170	3325	3480	3638	3890	4150	4405	4655			
LI	126	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3748	<LBS >	1970	2135	2295	2460	2620	2785	2945	3105	3265	3425	3585	3748	4010	4275	4535	4800			
LI	127	PSI >	32	35	38	41	44	47	50	53	56	59	62	65	70	75	80	85			
ML	3858	<LBS >	2025	2195	2365	2530	2700	2865	3030	3195	3365	3525	3690	3858	4130	4400	4670	4940			
LI	128	PSI >	32	35	38	41	44														

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low.

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

		8 PSI				E-load/10ply				F/12 for larger tires				given per tire				For Single-Load			
ML=maximum load,LI=Loadindex																					
LI	98	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1653	<LBS >	575	675	775	875	975	1070	1170	1265	1360	1460	1555	1653	1745	1840	1935	2030			
LI	99	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1709	<LBS >	595	700	800	905	1005	1105	1210	1310	1410	1510	1610	1709	1805	1905	2000	2100			
LI	100	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1764	<LBS >	615	720	825	935	1040	1145	1245	1350	1455	1555	1660	1764	1865	1965	2065	2165			
LI	101	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1819	<LBS >	630	745	855	960	1070	1180	1285	1395	1500	1605	1710	1819	1920	2025	2130	2235			
LI	102	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1874	<LBS >	650	765	880	990	1105	1215	1325	1435	1545	1655	1765	1874	1980	2090	2195	2300			
LI	103	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1929	<LBS >	670	790	905	1020	1135	1250	1365	1475	1590	1705	1815	1929	2040	2150	2260	2370			
LI	104	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	1984	<LBS >	690	810	930	1050	1170	1285	1405	1520	1635	1750	1865	1984	2095	2210	2325	2440			
LI	105	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2039	<LBS >	710	835	955	1080	1200	1320	1440	1560	1680	1800	1920	2039	2155	2270	2390	2505			
LI	106	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2094	<LBS >	730	855	980	1110	1235	1355	1480	1605	1725	1850	1970	2094	2210	2335	2455	2575			
LI	107	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2150	<LBS >	745	880	1010	1140	1265	1395	1520	1645	1775	1900	2025	2150	2270	2395	2520	2640			
LI	108	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2205	<LBS >	765	900	1035	1165	1300	1430	1560	1690	1820	1945	2075	2205	2330	2455	2585	2710			
LI	109	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2271	<LBS >	790	930	1065	1200	1335	1470	1605	1740	1875	2005	2135	2271	2400	2530	2660	2790			
LI	110	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2337	<LBS >	815	955	1095	1235	1375	1515	1655	1790	1925	2065	2200	2337	2470	2605	2740	2870			
LI	111	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2403	<LBS >	835	980	1125	1270	1415	1560	1700	1840	1980	2120	2260	2403	2540	2680	2815	2955			
LI	112	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2469	<LBS >	860	1010	1160	1305	1455	1600	1745	1890	2035	2180	2325	2469	2610	2750	2895	3035			
LI	113	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2535	<LBS >	880	1035	1190	1340	1495	1645	1795	1940	2090	2240	2385	2535	2680	2825	2970	3115			
LI	114	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2601	<LBS >	905	1065	1220	1375	1530	1685	1840	1995	2145	2295	2450	2601	2750	2900	3050	3195			
LI	115	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2679	<LBS >	930	1095	1255	1420	1580	1735	1895	2055	2210	2365	2520	2679	2830	2985	3140	3290			
LI	116	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2756	<LBS >	960	1125	1295	1460	1625	1785	1950	2110	2275	2435	2595	2756	2915	3070	3230	3385			
LI	117	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2833	<LBS >	985	1160	1330	1500	1670	1835	2005	2170	2335	2500	2665	2833	2995	3155	3320	3480			
LI	118	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2910	<LBS >	1010	1190	1365	1540	1715	1885	2060	2230	2400	2570	2740	2910	3075	3245	3410	3575			
LI	119	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	2998	<LBS >	1045	1225	1405	1585	1765	1945	2120	2295	2475	2650	2820	2998	3170	3340	3515	3685			
LI	120	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3086	<LBS >	1075	1260	1450	1635	1820	2000	2185	2365	2545	2725	2905	3086	3260	3440	3615	3795			
LI	121	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3197	<LBS >	1115	1310	1500	1695	1885	2075	2260	2450	2635	2825	3010	3197	3380	3565	3745	3930			
LI	122	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3307	<LBS >	1150	1355	1555	1750	1950	2145	2340	2535	2730	2920	3115	3307	3495	3685	3875	4065			
LI	123	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3417	<LBS >	1190	1400	1605	1810	2015	2215	2420	2620	2820	3020	3215	3417	3610	3810	4005	4200			
LI	124	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3527	<LBS >	1230	1445	1655	1870	2080	2290	2495	2705	2910	3115	3320	3527	3730	3930	4135	4335			
LI	125	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3638	<LBS >	1265	1490	1710	1925	2145	2360	2575	2790	3000	3215	3425	3638	3845	4055	4265	4470			
LI	126	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3748	<LBS >	1305	1535	1760	1985	2210	2430	2650	2875	3090	3310	3530	3748	3960	4180	4395	4605			
LI	127	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3858	<LBS >	1345	1580	1810	2045	2275	2505	2730	2955	3185	3410	3630	3858	4080	4300	4520	4745			
LI	128	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	3968	<LBS >	1380	1625	1865	2100	2340	2575	2810	3040	3275	3505	3735	3968	4195	4425	4650	4880			
LI	129	PSI >	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100			
ML	4079	<LBS >	1420	1670	1915	2160	2405	2645	2885	3125	3365	3605	3840	4079	4310	4545	4780	5015			
LI	130	PSI >	25	30	35	40															

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low.

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

		95 PSI				F-load/12ply				G-14 for larger tires				given per tire				For Single-Load			
ML=maximum load,LI=Loadindex																					
LI	100	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	1764	<LBS >	795	885	975	1065	1150	1240	1325	1415	1500	1590	1675	1764	1850	1935	2020	2105			
LI	101	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	1819	<LBS >	820	910	1005	1095	1185	1280	1370	1460	1550	1640	1725	1819	1905	1995	2080	2170			
LI	102	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	1874	<LBS >	845	940	1035	1130	1225	1315	1410	1505	1595	1690	1780	1874	1965	2055	2145	2235			
LI	103	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	1929	<LBS >	870	970	1065	1160	1260	1355	1450	1545	1640	1735	1830	1929	2020	2115	2210	2300			
LI	104	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	1984	<LBS >	895	995	1095	1195	1295	1395	1495	1590	1690	1785	1885	1984	2080	2175	2270	2370			
LI	105	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2039	<LBS >	920	1025	1125	1230	1330	1435	1535	1635	1735	1835	1935	2039	2135	2235	2335	2435			
LI	106	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2094	<LBS >	945	1050	1155	1260	1365	1470	1575	1680	1785	1885	1990	2094	2195	2295	2400	2500			
LI	107	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2150	<LBS >	970	1080	1190	1295	1405	1510	1620	1725	1830	1935	2040	2150	2250	2355	2460	2565			
LI	108	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2205	<LBS >	995	1105	1220	1330	1440	1550	1660	1770	1880	1985	2095	2205	2310	2420	2525	2630			
LI	109	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2271	<LBS >	1025	1140	1255	1370	1485	1595	1710	1820	1935	2045	2155	2271	2380	2490	2600	2710			
LI	110	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2337	<LBS >	1055	1175	1290	1410	1525	1645	1760	1875	1990	2105	2220	2337	2450	2560	2675	2790			
LI	111	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2403	<LBS >	1085	1205	1330	1450	1570	1690	1810	1930	2045	2165	2285	2403	2520	2635	2750	2870			
LI	112	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2469	<LBS >	1115	1240	1365	1490	1610	1735	1860	1980	2105	2225	2345	2469	2585	2705	2825	2945			
LI	113	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2535	<LBS >	1145	1270	1400	1530	1655	1780	1910	2035	2160	2285	2410	2535	2655	2780	2905	3025			
LI	114	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2601	<LBS >	1175	1305	1435	1570	1700	1830	1960	2085	2215	2345	2470	2601	2725	2850	2980	3105			
LI	115	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2679	<LBS >	1210	1345	1480	1615	1750	1885	2015	2150	2280	2415	2545	2679	2805	2940	3070	3200			
LI	116	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2756	<LBS >	1245	1385	1525	1660	1800	1940	2075	2210	2350	2485	2620	2756	2890	3020	3155	3290			
LI	117	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2833	<LBS >	1280	1420	1565	1710	1850	1990	2135	2275	2415	2555	2690	2833	2970	3105	3245	3380			
LI	118	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2910	<LBS >	1315	1460	1610	1755	1900	2045	2190	2335	2480	2620	2765	2910	3050	3190	3335	3475			
LI	119	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	2998	<LBS >	1355	1505	1655	1810	1960	2110	2255	2405	2555	2700	2850	2998	3140	3290	3435	3580			
LI	120	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3086	<LBS >	1395	1550	1705	1860	2015	2170	2325	2475	2630	2780	2930	3086	3235	3385	3535	3685			
LI	121	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3197	<LBS >	1445	1605	1765	1930	2090	2250	2405	2565	2725	2880	3040	3197	3350	3505	3660	3815			
LI	122	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3307	<LBS >	1490	1660	1830	1995	2160	2325	2490	2655	2815	2980	3145	3307	3465	3625	3790	3950			
LI	123	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3417	<LBS >	1540	1715	1890	2060	2230	2405	2575	2740	2910	3080	3245	3417	3580	3750	3915	4080			
LI	124	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3527	<LBS >	1590	1770	1950	2130	2305	2480	2655	2830	3005	3180	3350	3527	3695	3870	4040	4210			
LI	125	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3638	<LBS >	1640	1825	2010	2195	2375	2560	2740	2920	3100	3280	3455	3638	3815	3990	4165	4345			
LI	126	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3748	<LBS >	1690	1885	2070	2260	2450	2635	2825	3010	3195	3380	3560	3748	3930	4110	4295	4475			
LI	127	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3858	<LBS >	1740	1940	2135	2325	2520	2715	2905	3095	3285	3475	3665	3858	4045	4230	4420	4605			
LI	128	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	3968	<LBS >	1790	1995	2195	2395	2595	2790	2990	3185	3380	3575	3770	3968	4160	4355	4545	4740			
LI	129	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	4079	<LBS >	1840	2050	2255	2460	2665	2870	3070	3275	3475	3675	3875	4079	4275	4475	4675	4870			
LI	130	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	4189	<LBS >	1890	2105	2315	2525	2735	2945	3155	3365	3570	3775	3980	4189	4390	4595	4800	5000			
LI	131	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	4299	<LBS >	1940	2160	2375	2595	2810	3025	3240	3450	3665	3875	4085	4299	4505	4715	4925	5135			
LI	132	PSI >	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115			
ML	4409	<LBS >	1990																		

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low.

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

		110 PSI				G-load/14ply				H/16 for larger tires				given per tire				For Single-Load			
ML=maximum load,LI=Loadindex																					
LI	100	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	1764	<LBS >	925	1005	1080	1155	1235	1310	1385	1460	1535	1610	1685	1764	1835	1910	1985	2060			
LI	101	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	1819	<LBS >	955	1035	1115	1195	1270	1350	1430	1505	1585	1660	1740	1819	1895	1970	2045	2125			
LI	102	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	1874	<LBS >	985	1065	1150	1230	1310	1390	1470	1550	1635	1710	1790	1874	1950	2030	2110	2190			
LI	103	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	1929	<LBS >	1015	1100	1180	1265	1350	1435	1515	1600	1680	1765	1845	1929	2010	2090	2170	2250			
LI	104	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	1984	<LBS >	1045	1130	1215	1300	1390	1475	1560	1645	1730	1815	1895	1984	2065	2150	2235	2315			
LI	105	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2039	<LBS >	1070	1160	1250	1340	1425	1515	1600	1690	1775	1865	1950	2039	2125	2210	2295	2380			
LI	106	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2094	<LBS >	1100	1190	1285	1375	1465	1555	1645	1735	1825	1915	2005	2094	2180	2270	2355	2445			
LI	107	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2150	<LBS >	1130	1225	1320	1410	1505	1595	1690	1780	1875	1965	2055	2150	2240	2330	2420	2510			
LI	108	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2205	<LBS >	1160	1255	1350	1445	1545	1640	1735	1825	1920	2015	2110	2205	2295	2390	2480	2575			
LI	109	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2271	<LBS >	1195	1295	1390	1490	1590	1685	1785	1880	1980	2075	2170	2271	2365	2460	2555	2650			
LI	110	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2337	<LBS >	1230	1330	1435	1535	1635	1735	1835	1935	2035	2135	2235	2337	2435	2530	2630	2730			
LI	111	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2403	<LBS >	1265	1370	1475	1580	1680	1785	1890	1990	2095	2195	2300	2403	2500	2605	2705	2805			
LI	112	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2469	<LBS >	1300	1405	1515	1620	1730	1835	1940	2045	2150	2255	2360	2469	2570	2675	2780	2885			
LI	113	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2535	<LBS >	1335	1445	1555	1665	1775	1885	1990	2100	2210	2315	2425	2535	2640	2745	2855	2960			
LI	114	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2601	<LBS >	1370	1480	1595	1710	1820	1930	2045	2155	2265	2380	2490	2601	2710	2820	2930	3035			
LI	115	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2679	<LBS >	1410	1525	1645	1760	1875	1990	2105	2220	2335	2450	2565	2679	2790	2905	3015	3130			
LI	116	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2756	<LBS >	1450	1570	1690	1810	1930	2050	2165	2285	2400	2520	2635	2756	2870	2985	3105	3220			
LI	117	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2833	<LBS >	1490	1615	1735	1860	1985	2105	2225	2350	2470	2590	2710	2833	2950	3070	3190	3310			
LI	118	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2910	<LBS >	1530	1660	1785	1910	2035	2160	2285	2410	2535	2660	2785	2910	3030	3155	3275	3400			
LI	119	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	2998	<LBS >	1575	1710	1840	1970	2100	2230	2355	2485	2615	2740	2870	2998	3120	3250	3375	3500			
LI	120	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3086	<LBS >	1625	1760	1895	2025	2160	2295	2425	2560	2690	2820	2955	3086	3215	3345	3475	3605			
LI	121	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3197	<LBS >	1680	1820	1960	2100	2240	2375	2515	2650	2785	2925	3060	3197	3330	3465	3600	3735			
LI	122	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3307	<LBS >	1740	1885	2030	2170	2315	2460	2600	2740	2885	3025	3165	3307	3445	3585	3725	3860			
LI	123	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3417	<LBS >	1800	1945	2095	2245	2390	2540	2685	2835	2980	3125	3270	3417	3560	3705	3845	3990			
LI	124	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3527	<LBS >	1855	2010	2165	2315	2470	2620	2775	2925	3075	3225	3375	3527	3675	3825	3970	4120			
LI	125	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3638	<LBS >	1915	2075	2230	2390	2545	2705	2860	3015	3170	3325	3480	3638	3790	3945	4095	4250			
LI	126	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3748	<LBS >	1970	2135	2300	2460	2625	2785	2945	3105	3270	3425	3585	3748	3905	4060	4220	4380			
LI	127	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3858	<LBS >	2030	2200	2365	2535	2700	2870	3035	3200	3365	3530	3690	3858	4020	4180	4345	4505			
LI	128	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	3968	<LBS >	2090	2260	2435	2605	2780	2950	3120	3290	3460	3630	3795	3968	4135	4300	4470	4635			
LI	129	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	4079	<LBS >	2145	2325	2505	2680	2855	3030	3205	3380	3555	3730	3905	4079	4250	4420	4595	4765			
LI	130	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130			
ML	4189	<LBS >	2205	2390	2570	2750	2935	3115	3295	3475	3650	3830	4010	4189	4365	4540	4715	4895			
LI	131	PSI >	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125				

If actual load on tire or axle, and maximum load of tire, is given exact the pressure advice is save.

The maximum load given by the tire-maker is their responsibility, and for some tires this is to high given (low aspect ratio and off-road tires).

Determining the right actual load is your responsibility, and this is often judged to low. Also misreadings (use a light).

If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.

TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

		120 PSI				H-load/16ply				given per tire				For Single-Load				
ML=maximum load, LI=Loadindex																		
LI	110	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2337	<LBS >	1320	1415	1510	1600	1695	1785	1880	1970	2060	2150	2245	2337	2425	2515	2605	2695
LI	111	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2403	<LBS >	1360	1455	1550	1645	1740	1835	1930	2025	2120	2215	2305	2403	2495	2585	2680	2775
LI	112	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2469	<LBS >	1395	1495	1595	1690	1790	1885	1985	2080	2175	2275	2370	2469	2560	2660	2755	2850
LI	113	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2535	<LBS >	1435	1535	1635	1735	1835	1935	2035	2135	2235	2335	2435	2535	2630	2730	2825	2925
LI	114	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2601	<LBS >	1470	1575	1680	1780	1885	1985	2090	2190	2295	2395	2495	2601	2700	2800	2900	3000
LI	115	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2679	<LBS >	1515	1620	1730	1835	1940	2045	2155	2260	2365	2470	2570	2679	2780	2885	2990	3090
LI	116	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2756	<LBS >	1560	1670	1780	1890	1995	2105	2215	2325	2430	2540	2645	2756	2860	2965	3075	3180
LI	117	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2833	<LBS >	1600	1715	1830	1940	2055	2165	2275	2390	2500	2610	2720	2833	2940	3050	3160	3270
LI	118	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2910	<LBS >	1645	1760	1880	1995	2110	2225	2340	2455	2565	2680	2795	2910	3020	3135	3245	3360
LI	119	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	2998	<LBS >	1695	1815	1935	2055	2175	2290	2410	2525	2645	2760	2880	2998	3110	3230	3345	3460
LI	120	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3086	<LBS >	1745	1870	1990	2115	2235	2360	2480	2600	2720	2845	2965	3086	3205	3325	3440	3560
LI	121	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3197	<LBS >	1810	1935	2065	2190	2315	2445	2570	2695	2820	2945	3070	3197	3320	3445	3565	3690
LI	122	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3307	<LBS >	1870	2000	2135	2265	2395	2530	2660	2790	2915	3045	3175	3307	3435	3560	3690	3815
LI	123	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3417	<LBS >	1930	2070	2205	2340	2475	2610	2745	2880	3015	3150	3280	3417	3545	3680	3810	3945
LI	124	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3527	<LBS >	1995	2135	2275	2415	2555	2695	2835	2975	3110	3250	3385	3527	3660	3800	3935	4070
LI	125	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3638	<LBS >	2060	2205	2350	2495	2635	2780	2925	3065	3210	3350	3495	3638	3775	3920	4060	4200
LI	126	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3748	<LBS >	2120	2270	2420	2570	2715	2865	3015	3160	3305	3455	3600	3748	3890	4035	4180	4325
LI	127	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3858	<LBS >	2180	2335	2490	2645	2795	2950	3100	3255	3405	3555	3705	3858	4005	4155	4305	4455
LI	128	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	3968	<LBS >	2245	2405	2560	2720	2875	3035	3190	3345	3500	3655	3810	3968	4120	4275	4425	4580
LI	129	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4079	<LBS >	2305	2470	2635	2795	2955	3120	3280	3440	3600	3760	3920	4079	4235	4395	4550	4710
LI	130	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4189	<LBS >	2370	2535	2705	2870	3035	3200	3365	3530	3695	3860	4025	4189	4350	4510	4675	4835
LI	131	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4299	<LBS >	2430	2605	2775	2945	3115	3285	3455	3625	3795	3960	4130	4299	4465	4630	4795	4965
LI	132	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4409	<LBS >	2495	2670	2845	3020	3195	3370	3545	3720	3890	4065	4235	4409	4580	4750	4920	5090
LI	133	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4542	<LBS >	2570	2750	2930	3115	3295	3470	3650	3830	4010	4185	4365	4542	4715	4890	5070	5245
LI	134	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4674	<LBS >	2645	2830	3020	3205	3390	3575	3760	3940	4125	4305	4490	4674	4855	5035	5215	5395
LI	135	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4806	<LBS >	2720	2910	3105	3295	3485	3675	3865	4055	4240	4430	4615	4806	4990	5175	5365	5550
LI	136	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	4938	<LBS >	2795	2990	3190	3385	3580	3775	3970	4165	4355	4550	4745	4938	5125	5320	5510	5700
LI	137	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	5071	<LBS >	2870	3070	3275	3475	3675	3875	4075	4275	4475	4675	4870	5071	5265	5460	5660	5855
LI	138	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	5203	<LBS >	2945	3150	3360	3565	3770	3980	4185	4390	4590	4795	5000	5203	5405	5605	5805	6005
LI	139	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	5357	<LBS >	3030	3245	3460	3670	3885	4095	4305	4515	4725	4935	5145	5357	5565	5770	5980	6185
LI	140	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	5512	<LBS >	3120	3340	3560	3780	3995	4215	4430	4650	4865	5080	5295	5512	5725	5935	6150	6365
LI	141	PSI >	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140
ML	5677	<LBS >	3210	3440	3665	3890	4115	4340	4565	4785	5010	5230	5455	5677	5895	6115	63	