

Select
the level of
protection
your RV
needs.

30A
Portable
44740



30A
Portable
AECM
10086



30A
Portable
with LCD
34730



30A
Hardwire
34520



50A
Portable
with LCD
34750



50A
Hardwire
34560



50A
Hardwire
40240



Over/Under Voltage			●	●	●	●	●
Open Neutral Protection			●	●	●	●	●
Reverse Polarity Protection			●	●	●	●	●
Miswired Pedestal Indication		●	●	●	●	●	●
Ground Fault Protection	●						
Dangerous Current on Ground Wire Indication			●	●	●	●	
Time Delay at Power Up (2 min. 15 sec.)			●	●	●	●	●
Remote Display							●
Built-In LCD Display			●		●		
Weather Resistant	●	●	●		●		
UL Listed				●		●	●
Source Power Connection Diagnostics							●
Lock Hasp Available	●		●		●		
Cord Gauge	10/3	N/A	10/3	N/A	6/4	N/A	N/A
Electrical Rating	120V, 30A	120V, 30A	120V, 30A	120V, 30A	120/240V 50A	120/240V 50A	120/240V 50A
Surge Suppression (Joules)	510	1,020	2,450	1,050	3,850	1,750	3,350
Max Spike Current	1,250A	N/A	6,500A	6,500A	6,500A	6,500A	130,000A

Select the level of protection your RV needs.

50A
Basic Protection
40100



50A
Limited Protection
41260



50A
Full Protection
40250-RVC



90A
Full Protection
41290-RVC



Select the level of protection your RV needs.	50A Basic Protection 40100	50A Limited Protection 41260	50A Full Protection 40250-RVC	90A Full Protection 41290-RVC
Over/Under Voltage			●	●
Open Neutral Protection		●	●	●
Reverse Polarity Protection		●	●	●
Miswired Pedestal Indication			●	●
Ground Monitoring			●	●
Time Delay at Power Up	●	●	●	●
Remote Display (Optional)			●	●
Amperage Measurement			●	●
Third Party Listed	●	●	●	
Source Power Connection Diagnostics			●	●
Generator Dominant	●	●	●	●
Mechanical Interlocking Contactors	●	●	●	●
Electrical Rating	120/240V, 50A	120/240V, 50A	120/240V, 50A	120/240V, 90A
Surge Suppression (Joules)	N/A	2,600	3,350	3,350
Max Spike Current	N/A	76,400A	130,000A	130,000A
Contactor Rating	50A, FLA	50A, FLA	65A, FLA	95A, FLA
UL Standard	UL 1008	UL 1008	UL 1008	N/A