

SECTION 5

PLUMBING

that the tank contains. Sometimes, residue on the sides of a tank, or water with a low mineral content will give a false reading.

Check the levels occasionally when you are sure of a tank's contents and compare it to the reading on the monitor panel. If you are concerned about the accuracy of the monitor panel, have it checked at your local Service Center.

NOTE: REMEMBER THAT THE MONITOR PANEL HAS ADDITIONAL FUNCTIONS, SUCH AS DISPLAYING BATTERY AND LP LEVELS.

Sanitizing the Fresh Water System

Sanitize the system before initial use, after extended periods of non-use, at least once a year during continuous use, and if there is suspicion that the system has been contaminated.



WATER PUMP

To Sanitize the System:

- Prepare a chlorine solution using a gallon of water and $\frac{1}{4}$ cup of liquid household bleach, (5% sodium hypochlorinate solution.) Use one gallon of solution for each 15 gallons of tank capacity.
- With an empty tank and all faucets and drains closed, pour the solution into the fresh water tank.
- Completely fill the tank with fresh water.
- Switch on the water pump. Open all faucets one at a time until all air is purged and the water flows freely.
- Again, add fresh water to the tank until the water level reaches the fill spout.
- Allow the solution to stand in the tank, undisturbed, for at least 3 (three) hours.
- Drain the system by opening all faucets and the fresh water tank drain valve, while flushing the system with fresh water of drinking quality.
- Continue flushing the system, allowing the water to flow for several minutes.
- Close the tank drain valve and all faucets. Refill the system with water of known drinking quality.

NOTES:
