If actual load on tire or axle,and maximum load of tire, is given exact the pressure advice is save.
The maximum load given by the tire-maker is their responcibility, and for some tires this is to high given (low aspect ratio and off-road tires).
Determining the right actual load is your responcibility, and this is often judged to low.
If in red, the pressure is higher then the reference-pressure (maxloadpressure) wich is not the maximum pressure.
TRA allows up to 10 psi more for LT tires and 20 PSI more for Truck-tires, but dont support the higher load then maximum load for speed.

110 PSI **G-load/14ply** H/16 larger tires **given per tire** **For Single-Load**

	Max load														
LI	1521	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
95	LBS	930	1000	1065	1130	1195	1260	1325	1390	1455	**1521**	1585	1645	1710	1775
LI	1565	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
96	LBS	960	1025	1095	1160	1230	1295	1365	1430	1495	**1565**	1630	1695	1760	1825
LI	1609	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
97	0	985	1055	1125	1195	1265	1335	1400	1470	1540	**1609**	1675	1745	1810	1880
LI	1653	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
98	0	1015	1085	1155	1225	1300	1370	1440	1510	1580	**1653**	1720	1790	1860	1930
LI	1709	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
99	0	1045	1120	1195	1270	1340	1415	1490	1560	1635	**1709**	1780	1850	1925	1995
LI	1764	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
100	0	1080	1155	1235	1310	1385	1460	1535	1610	1685	**1764**	1835	1910	1985	2060
LI	1819	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
101	110	1115	1195	1270	1350	1430	1505	1585	1660	1740	**1819**	1895	1970	2045	2125
LI	1874	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
102	110	1150	1230	1310	1390	1470	1550	1635	1710	1790	**1874**	1950	2030	2110	2190
LI	1929	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
103	110	1180	1265	1350	1435	1515	1600	1680	1765	1845	**1929**	2010	2090	2170	2250
LI	1984	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
104	110	1215	1300	1390	1475	1560	1645	1730	1815	1895	**1984**	2065	2150	2235	2315
LI	2039	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
105	110	1250	1340	1425	1515	1600	1690	1775	1865	1950	**2039**	2125	2210	2295	2380
LI	2094	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
106	110	1285	1375	1465	1555	1645	1735	1825	1915	2005	**2094**	2180	2270	2355	2445
LI	2150	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
107	110	1320	1410	1505	1595	1690	1780	1875	1965	2055	**2150**	2240	2330	2420	2510
LI	2205	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
108	110	1350	1445	1545	1640	1735	1825	1920	2015	2110	**2205**	2295	2390	2480	2575
LI	2271	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
109	110	1390	1490	1590	1685	1785	1880	1980	2075	2170	**2271**	2365	2460	2555	2650
LI	2337	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
110	110	1435	1535	1635	1735	1835	1935	2035	2135	2235	**2337**	2435	2530	2630	2730
LI	2403	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
111	110	1475	1580	1680	1785	1890	1990	2095	2195	2300	**2403**	2500	2605	2705	2805
LI	2469	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
112	110	1515	1620	1730	1835	1940	2045	2150	2255	2360	**2469**	2570	2675	2780	2885
LI	2535	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
113	110	1555	1665	1775	1885	1990	2100	2210	2315	2425	**2535**	2640	2745	2855	2960
LI	2601	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
114	110	1595	1710	1820	1930	2045	2155	2265	2380	2490	**2601**	2710	2820	2930	3035
LI	2679	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
115	110	1645	1760	1875	1990	2105	2220	2335	2450	2565	**2679**	2790	2905	3015	3130
LI	2756	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
116	110	1690	1810	1930	2050	2165	2285	2400	2520	2635	**2756**	2870	2985	3105	3220
LI	2833	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
117	110	1735	1860	1985	2105	2225	2350	2470	2590	2710	**2833**	2950	3070	3190	3310
LI	2910	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
118	110	1785	1910	2035	2160	2285	2410	2535	2660	2785	**2910**	3030	3155	3275	3400
LI	2998	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
119	110	1840	1970	2100	2230	2355	2485	2615	2740	2870	**2998**	3120	3250	3375	3500
LI	3086	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
120	110	1895	2025	2160	2295	2425	2560	2690	2820	2955	**3086**	3215	3345	3475	3605
LI	3197	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
121	110	1960	2100	2240	2375	2515	2650	2785	2925	3060	**3197**	3330	3465	3600	3735
LI	3307	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
122	110	2030	2170	2315	2460	2600	2740	2885	3025	3165	**3307**	3445	3585	3725	3860
LI	3417	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
123	110	2095	2245	2390	2540	2685	2835	2980	3125	3270	**3417**	3560	3705	3845	3990
LI	3527	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
124	110	2165	2315	2470	2620	2775	2925	3075	3225	3375	**3527**	3675	3825	3970	4120
LI	3638	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
125	110	2230	2390	2545	2705	2860	3015	3170	3325	3480	**3638**	3790	3945	4095	4250
LI	3748	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
126	110	2300	2460	2625	2785	2945	3105	3270	3425	3585	**3748**	3905	4060	4220	4380
LI	3858	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
127	110	2365	2535	2700	2870	3035	3200	3365	3530	3690	**3858**	4020	4180	4345	4505
LI	3968	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
128	110	2435	2605	2780	2950	3120	3290	3460	3630	3795	**3968**	4135	4300	4470	4635
LI	4079	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
129	110	2505	2680	2855	3030	3205	3380	3555	3730	3905	**4079**	4250	4420	4595	4765
LI	4189	65	70	75	80	85	90	95	100	105	**110**	115	120	125	130
130	110	2570	2750	2935	3115	3295	3475	3650	3830	4010	**4189**	4365	4540	4715	4895