

Hook up for Towing

- ☐ Make sure hitch is in receiver and locked
- ☐ Raise trailer tongue high enough to clear hitch
- ☐ Back up truck
- ☐ Unlock coupler latch and raise
- ☐ Lower coupler onto hitch and ensure it seats properly
- ☐ Lower coupler latch and lock
- ☐ Attach plug
- ☐ Attach chains in "X" pattern
- ☐ Attach brake cable karabiner to truck
- ☐ Attach sway bar and tighten (2-finger tight and ½ turn more)
- ☐ Ensure sway bar lever will not hit bumper in a turn
- ☐ Retract dolly almost fully (if fully retracted, pin will not come out)
- ☐ Remove dolly wheel and stow
- ☐ Remove chocks and stow
- ☐ Ensure all doors, top and storage are latched and locked
- ☐ Ensure stabilizer jacks are up and tight
- ☐ Ensure hoses and power chord are disconnected and stowed
- ☐ Check LP tank closed
- ☐ Set up rear view camera in truck
- ☐ Drive off

Parking Trailer

- ☐ REMOVE SWAY BAR
- ☐ Back in Trailer
- ☐ Chock Tires
- ☐ Attach dolly wheel
- ☐ Unlock coupler latch
- ☐ Put dolly wheel chock on ground
- ☐ Crank down dolly wheel and remove from hitch
- ☐ Remove plug, chains and brake cable and stow on tongue
- ☐ Relock coupler latch
- ☐ Park truck

Camper Set-Up

- ☐ Level trailer sideways with BAL leveler; stow ratchet
- ☐ Level trailer length-wise
- ☐ Crank down stabilizers
- ☐ Stow crank
- ☐ Unlock top
- ☐ Crank up top until red cable is taut (do not back off on crank)
- ☐ Stow crank
- ☐ Put safety guards on lifter posts
- ☐ Pull dinette canvas out and let hang outside of trailer
- ☐ Put front bunk support bars on trailer
- ☐ Pull out front bunk
- ☐ Pull out rear bunk
- ☐ Install rear bunk support bars
- ☐ Pull out dinette slide out
- ☐ Pull out door step
- ☐ Install door
- ☐ Zip the 4 corners shut on the inside
- ☐ Put in canvas support bars on bunks and dinette
- ☐ Attach canvas to bunks and dinette
- ☐ Attach bunk bungee chords
- ☐ Close 4 corners on outside
- ☐ Install 4 cotter pins in front bunk and dinette
- ☐ Set up couch
- ☐ Set up stove
- ☐ Set up table
- ☐ Stuff bags in open holes
- ☐ Put steel wool where dinette and camper join
- ☐ Spray bug spray around stabilizers and wheels
- ☐ Ensure sink cover is removed
- ☐ Check stove knobs and pilot lights are "Off"
- ☐ Hook up power and water
- ☐ Switch refrigerator to 120v
- ☐ Turn on LP tank
- ☐ If lighting water heater, light stove first
- ☐ Ensure water heater has water flowing to it (as needed)
- ☐ Light water heater (as needed)

Camper Breakdown

- ☐ Stow all loose items in camper
- ☐ Turn off water pump (as necessary)
- ☐ Turn off stove (as necessary)
- ☐ Turn off furnace (as necessary)
- ☐ Turn off hot water heater and pilot light (as necessary)
- ☐ Turn refrigerator to 12v power (Turn off LP and pilot as necessary)
- ☐ Close LP tank
- ☐ Unplug 30-amp power chord and stow
- ☐ Remove water hose and stow
- ☐ Drain water from tanks (as necessary)
- ☐ Dump cassette toilet and replace (as necessary)
- ☐ Purge gas from stove line
- ☐ Ensure stove is cool and that all knobs are set to "Off"
- ☐ Ensure all windows are closed and zipped
- ☐ Fold down shower
- ☐ Fold down table
- ☐ Fold down sofa
- ☐ Remove overhead pantry and wardrobe and stow
- ☐ Turn off all lights and stow
- ☐ Turn off ceiling fan and close lid
- ☐ Fold down sink/stove (stow sink cover under dinette cushion)
- ☐ Turn off A/C and unplug. Place chord on dinette slide
- ☐ Remove all 4 cotter pins (from front bunk and dinette slide)
- ☐ Remove and stow door
- ☐ Unzip 4 tent corners
- ☐ Remove canvas support bars from bunk ends and dinette and stow
- ☐ Remove 2 safety guards from lifter posts and stow
- ☐ Undo canvas from slide out
- ☐ Remove steel wool from dinette corners
- ☐ Push in slide out
- ☐ Pull slide out canvas out and let hang outside of camper
- ☐ Undo rear bunk canvas and fold in
- ☐ Remove rear bunk support bars and stow
- ☐ Push in rear bunk (watch out for A/C chord)
- ☐ Undo front bunk canvas and fold in
- ☐ Push in front bunk
- ☐ Remove front bunk support bars and stow
- ☐ Fold dinette canvas in
- ☐ Make final check roof fan is closed
- ☐ Stow door step and close camper door
- ☐ Crank down top
- ☐ Secure top and storage lid with latches and locks; tighten cable slightly
- ☐ Stow crank
- ☐ Raise stabilizers and stow stabilizer crank
- ☐ Replace BAL leveler with chocks; stow BAL Leveler and ratchet