

# Sailun Tire

Continued from page 1

SPECIAL ST METRIC TIRES FOR TRAILERS IN HIGHWAY SERVICE

TIRE AND RIM ASSOCIATION STANDARD

TIRE LOAD LIMITS (lbs.) AT VARIOUS COLD INFLATION PRESSURES (psi)

Tire Size	USAGE	70	75	80	85	90	95	100	105	110
<b>75 SERIES</b>										
ST225/75R15	DUAL									
	SINGLE	2620	2720	<b>2830 (E) 117</b>						
<b>80 SERIES</b>										
ST215/80R16	DUAL	2360	2470	<b>2540 (E) 113</b>						
	SINGLE	2690	2800	<b>2910 (E) 118</b>						
ST235/80R16	DUAL	2760	2870	<b>3000 (E) 119</b>	3085	3195	<b>3305 (F) 122</b>	3415	3525	<b>3640 (G) 125</b>
	SINGLE	3140	3260	<b>3420 (E) 123</b>	3525	3640	<b>3750 (F) 126</b>	3860	3970	<b>4080 (G) 129</b>
<b>85 SERIES</b>										
ST235/85R16	DUAL	2950	3060	<b>3200 (E) 121</b>	3305	3415	<b>3525 (F) 124</b>	3640	3750	<b>3860 (G) 127</b>
	SINGLE	3360	3480	<b>3640 (E) 125</b>	3750	3860	<b>3970 (F) 128</b>	4080	4190	<b>4400 (G) 132</b>
<b>90 SERIES</b>										
ST205/90R15	DUAL	2360	2470	<b>2540 (E) 113</b>						
	SINGLE	2690	2800	<b>2910 (E) 118</b>						
ST225/90R16	DUAL	2910	3020	<b>3080 (E) 120</b>						
	SINGLE	3300	3440	<b>3520 (E) 124</b>						

Note: 1 **Bold** face loads in the above tables are maximum for the tire size and load range shown. Numbers after the load range parentheses are international Load Index numbers.

2 Above inflation pressures are minimum for the loads shown.

3 For tires not marked with a Service Description, consult tire manufacturer for applications above 65 mph (105 km/h)

4 Sailun S637 is rated for 75 mph (120 km/h)

Consult trailer manufacturer specification for wheel and axle capacity.